

DuploCOLL® 5015

Art. No. 11 751 L 01

Double-sided pressure sensitive adhesive mounting tape with a modified acrylic adhesive and a compressible foam carrier

Product construction			
	Name	Colour	Thickness [mm]
Liner	Silicone paper	yellow	approx. 0,08
Adhesive covered side	Modified acrylic		
Carrier	Polyethylene foam	white	approx. 0,45
Adhesive open side	Modified acrylic		
Total thickness:			approx. 0,53

Product advantages

- High initial adhesion (tack)
- High shear strength
- Excellent resistance to ageing, weathering and UV-radiation
- Extensive resistance to the influence of chemicals and solvents (domestic cleaners and polishing agents)
- On account of its compressible and elastic foam carrier the adhesive tape assures a perfect adaptation to surfaces by compensating for different expansion coefficients of the substrates that are joined.
- Suitable for indoor and outdoor applications on smooth and slightly rough surfaces.

Main application fields

- Self-adhesive preparation of extruded plastic and cover profiles for a permanent mounting in the furniture industry
- Mounting of decorative parts, doublings, stay bars on the most various decoration surfaces and on glass
- Fastening of face plates, holders and cable ducts in the phono-, household appliances-, and electro industry
- Self-adhesive preparation of nameplates and signs
- Mounting of exterior and interior mirrors in plastic housings in the automotive industry. Shatter protection!

Product features	Applicability on
Initial adhesion	Foam
Final adhesion	Rubber
Dimensional stability	Fabric
Adhesion on even surfaces	Glass/Ceramics
Adhesion on rough surfaces	Wood
Ageing resistance	High energy plastics: PVC, PC, ABS,...
Weathering resistance	Low energy plastics: PE, PP,...
Chemical resistance	Metal
Resistance to plasticizers	Paper/Cardboard
● ● ● very suitable	○ ○ ○ not suitable
● ● ○ suitable	
● ○ ○ suitable with reductions	

DuploCOLL® 5015

Art. No. 11 751 L 01

Double-sided pressure sensitive adhesive mounting tape with a modified acrylic adhesive and a compressible foam carrier

Specific technical data*

Temperature range -40 °C to +90 °C

Adhesive strength in accordance with DIN EN 1939 after 24 hours at room temperature on different substrates:

Polypropylene 11 N/25 mm

Polyethylene 5 N/25 mm

PVC 29 N/25 mm

Adhesive strength at room temperature in accordance with DIN EN 1939 after 7 days at 38 °C and 100 % relative humidity of air on steel:

38 N/25 mm

* Specific test results, statistically not approved.


DuploCOLL® 5015

Art. No. 11 571 L 01

Double-sided pressure sensitive adhesive mounting tape with a modified acrylic adhesive and a compressible foam carrier

Technical Data

Shear strength	on steel according to DIN EN 1943, edition 1996, at +23 °C +/- 2°C	40 N/625 mm ²
Peel strength	on steel according to DIN EN 1939, edition 1996, at +23 °C +/- 2°C	45 N/25 mm



Application

Recommended application temperature 18 °C to 35 °C

Application guidelines www.lohmann-tapes.com

Storage

Adhesive tapes should be stored at room temperature and normal humidity (50-70 %).
The storage stability is one year after delivery.

Product presentation

Converted product	Rolls		
Width [mm]	> 6	> 12	
Length [m]	50	100/200	
Max. log width: 1260 mm	Other dimensions, die-cuts and sheets on request.		

For mechanical mounting of this adhesive tape we also offer a wide range of application devices.

The physical characteristics contained in our data sheets represent typical or average values. They do not represent any warranties or guarantees and must not be used for technical specification purposes. All application related statements, information and recommendations herein are given to the best of our knowledge and practical experience. The buyer is responsible for determining the suitability of the specific tape for its intended use in connection with user's method of application. Please consult our Technical Applications Department for specific advice. Our general Term and Conditions of Sale apply, particularly with regard to warranty and liability.

Date of issue: May 2011

Lohmann GmbH & Co. KG
Irlicher Strasse 55
56567 Neuwied
Germany
Phone: + 49 (0) 26 31 34 - 0
Fax: + 49 (0) 26 31 34 - 6661
E-mail: info@lohmann-tapes.com

For further Information
www.lohmann-tapes.com



Concerning product safety (confirmation, conformity to guidelines, REACH, etc.) please use the following
E-mail address: products.safety@lohmann-tapes.com